

STONE PRO MAINTENANCE CRYSTALLIZER marble polish is designed to easily maintain the shine on polished marble, travertine, and limestone; It is also used for granite countertop maintenance. This product will harden the surface making it more durable, scratch resistant, and less slippery.

EQUIPMENT NEEDED (Countertops & Bath):

- Variable Speed Polisher. 500- 800 RPMs only
- Hook & Loop Backing Plate
- Maintenance Crystallizer marble polish (Crystallizer)
- Steel Wool Pads (#2 or finer)
- Read
 - 1. **HOW TO POLISH MARBLE.PDF** and
 - 2. **HOW TO POLISH GRANITE.PDF** for more instruction on the polishing process.



POLISHING INSTRUCTIONS:

1. Test in an inconspicuous place.
2. Thoroughly clean the surfaces to be treated with **Crystal Clean**.
3. Shake **Maintenance Crystallizer** well before using bottle. Shake often during use. Adjust nozzle to slight stream spray.
4. Place #2 steel wool pad onto polisher backing plate.
5. Define a manageable work space. Recommended: 3 ft x3 ft.
6. Spray 3 or 4 squirts of **Maintenance Crystallizer** onto the surface.
7. Buff at 175 RPM with a side to side motion until dry. Do not over buff.
8. Repeat process until desired shine is achieved. For the first application, more treatments will be needed to obtain desired shine.
9. When all areas have been treated, use hand steel wool pads to buff corners and edges to remove residue and even out the shine. Remove polish residue and shavings.
10. Light colored grout joints may darken if steel wool pads are over used, or if too much crystallizer is used.

COVERAGE RATES:

1 Gal. 1000 – 4000 sq ft, changing steel wool every 75 to 150 sq ft.

HOW IT WORKS:

The magnesium fluorosilicate in the crystallizer bonds with the calcium in marble and other natural stones, resulting in a newly formed layer of calcium which is very hard, dense, and clear. The polishing action of the steel wool activates the new crystal layer.

WARNING:

Surface must be dry prior to use. After polishing, clean up steel wool fragments. Otherwise, they will rust onto the surface. Avoid contact with eyes or skin. Use only with rubber gloves. Wear dust mask. Contains Magnesium Silicofluoride.



FIRST AID:

Call physician immediately. **Eyes:** Flush with water for 15 minutes. Call physician. **Skin:** Wash with soapy water. Clean under fingernails. **Ingestion:** Drink large amounts of water, follow with mineral oil or egg whites. **Inhalation:** Get person to fresh air. If unconscious, call physician. **KEEP OUT OF REACH OF CHILDREN**



Distributed by: JFlint Products, Co. 68805 Perez Rd. F-42 Cathedral City Ca 92234 (760) 770-3014